

#### US009638517B2

# (12) United States Patent Bondurant et al.

## (54) OPTICAL THREAD PROFILER

(71) Applicant: Quest Metrology, LLC, Kent, WA

(US)

(72) Inventors: Phillip Dewayne Bondurant,

Covington, WA (US); David William Rook, Kent, WA (US); David H. Bothell, Lake Tapps, WA (US); Christian Robert Lentz, Benton City, WA (US); David Jack Savage, Renton,

WA (US)

(73) Assignee: Quest Metrology, LLC, Kent, WA

(US)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 14/962,922

(22) Filed: Dec. 8, 2015

(65) Prior Publication Data

US 2016/0091303 A1 Mar. 31, 2016

## Related U.S. Application Data

- (63) Continuation of application No. 14/474,067, filed on Aug. 29, 2014, now Pat. No. 9,234,748, which is a continuation of application No. 13/493,806, filed on Jun. 11, 2012, now Pat. No. 8,860,952.
- (60) Provisional application No. 61/495,083, filed on Jun. 9, 2011.
- (51) **Int. Cl. G01B 11/24** (2006.01)

(10) Patent No.: US 9,638,517 B2

(45) **Date of Patent:** \*May 2, 2017

(52) U.S. Cl. CPC ......... *G01B 11/2425* (2013.01); *G01B 11/24* 

(58) Field of Classification Search

CPC . G01B 11/24; G01B 11/2425; G01B 11/2518; G01B 11/2426; G01B 11/255; G01B 5/20; G01B 5/163; G01B 5/166

### (56) References Cited

### U.S. PATENT DOCUMENTS

3,924,953 A	12/1975	Allard
4,315,688 A	2/1982	Pryor
4,644,394 A	2/1987	Reeves
5,521,707 A		Castore
5,571,222 A	11/1996	Ludwig
7,490,411 B2	2/2009	Matsumiya
	(Continued)	

#### OTHER PUBLICATIONS

International Search Report and Written Opinion mailed Aug. 6, 2012, in International Patent Application No. PCT/US2012/041932, filed Jun. 11, 2012, 8 pages.

(Continued)

Primary Examiner — Hoa Pham (74) Attorney, Agent, or Firm — Christensen O'Connor Johnson Kindness PLLC

### (57) ABSTRACT

An apparatus configured to measure at least one physical characteristic of a threaded surface (e.g., an internally threaded surface) of an object is provided. The apparatus uses optical triangulation to perform non-contact characterization of the threaded surface. The apparatus can be used to characterize various aspects of the threaded surface, including generating the measurements required to produce a longitudinal cross-sectional profile of the threaded surface.

# 25 Claims, 16 Drawing Sheets

